2 - Position Hotplate LX201THP

Email: info@labdex.com **website:** www.labdex.com

Description

2 - Position Hotplate LX201THP is a 2 position benchtop device with a heating temperature range of Rt-325°C. Built-in ceramic-coated aluminum (black), PID auto control, digital LED display, PT100, with an inner and outer thermocouple. Hotplate are used in chemistry and biology lab for uniformly heating of solutions and materials.

Specifications

Max stirring volume	2 x 50ml - 5000ml
Max temperature for top plate	RT~325°C
Temperature control	PID control
Top plate dimension	180 x 180 mm
Temperature range for machine	Ambient to 325°C
Temperature display (°C)	LED digital display
Temperature accuracy	+/- 1 degree
Permissible ambient temperature	40°C
Thermocouple probe / sensor type	Inner and outer thermocouple with PT100
Heating power	550 W
Voltage	160 - 240V, or 110 - 130V
Packing dimension (L × W × H)	480 x 380 x 280 mm
Gross weight	16 kg

Features

- Reliable and easy to operate
- Equipped with digital LED display and PID auto control system
- It has PT100 sensor with Inner and outer thermocouple
- Ceramic coated aluminum heating plate for heat distribution and corrosion resistance
- Adjustable temperature control
- The shell material is aluminum alloy
- Having 2 - position intelligent hotplate for easy testing

Applications

- Used to uniformly heat samples and homogenized samples or solutions.

Standard Accessories

Accessories No.	Specifications
1	Removable holder x 2 pcs, Length: 500mm Diameter: 10mm, Material: Stainless steel
2	Clamp with screw x 2 pcs
3	Inner thermocouple (4-spin) x 2 pcs
4	Outer thermocouple x 2 pcs
5	4 Prong stainless steel clamp opens to 3 1/2” x 2 pcs

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com